

## TSF437

メチルフェニルシリコーンオイル

TSF437は、低粘度のメチルフェニルシリコーンオイルで、プラスチックの内部添加タイプの離型剤として使用されます。

### 特 長

- 離型性に優れています。
- 潤滑性に優れています。
- 化学的に不活性です。

### 用 途

- プラスチック用添加剤

### 特性例

項 目	特性値
外 観	無色透明
比重 (25°C)	1.02
粘度 (25°C) mm <sup>2</sup> /s{cSt}	22{22}
屈折率 (n <sub>D</sub> <sup>25</sup> )	1.499
引火点 °C	170
流動点 °C	-60以下
表面張力 (25°C) mN/m	24.2
誘電率 (60Hz、25°C)	2.8
誘電正接 (60Hz、25°C)	0.001
体膨張係数 1/K	8.7×10 <sup>-4</sup>

### シリコーンオイルの相互溶解性

製品名	ジメチルシリコーンオイル		メチルフェニルシリコーンオイル			
	TSF405	TSF451-100	TSF431	TSF433	TSF437	TSF4300
TSF405		○	○	○	○	○
TSF451-100	○		○	×	×	×
TSF431	○	○		×	△	△
TSF433	○	×	×		○	○
TSF437	○	×	△	○		○
TSF4300	○	×	△	○	○	

注) ○：相溶性あり      △：TSF431が90%以上の場合相溶      ×：相溶性なし

### 使用方法

TSF437をそのまま、あるいはあらかじめマスターバッチ化して、樹脂に対して0.01-0.5重量%添加し、均一に分散させてください。

### 取扱い上の注意

- 取扱い時には、保護眼鏡および必要に応じて保護手袋を着用してください。
- 換気のよい所で使用してください。

**保管**

- 直射日光を避け、湿気の少ない冷暗所に保管してください。
- 子供の手の届かない所に保管してください。

**荷姿・梱包**

- 1kgポリビン(1ケース10P入り)
- 15kg石油缶
- 200kgドラム

**消防法**

危険物第4類第3石油類

**Contact Information**

Email

[commercial.services@momentive.com](mailto:commercial.services@momentive.com)

**Telephone****Americas**

+1 800 295 2392

Toll free\*

+704 805 6946

Direct Number

\*All American countries

**Latin America****Brazil**

+55 11 4534 9650

Direct Number

**Mexico**

+52 55 2169 7670

Direct Number

**EMEAL- Europe, Middle East, Africa & India****Europe**

+390510924300

Direct number

**India, Middle East & Africa**

+ 91 44 71212207

Direct number\*

\*All Middle Eastern countries, Africa, India,

**ASIA PACIFIC****China**

800 820 0202

Toll free

+86 21 3860 4892

Direct number

**Japan**

+81 3 5544 3111

Direct number

**Korea**

+82 2 6201 4600

For literature and technical assistance, visit our website at: [www.momentive.com](http://www.momentive.com)

**DISCLAIMER:**

THE MATERIALS, PRODUCTS AND SERVICES OF MOMENTIVE PERFORMANCE MATERIALS INC. AND ITS SUBSIDIARIES AND AFFILIATES (COLLECTIVELY "SUPPLIER"), ARE SOLD SUBJECT TO SUPPLIER'S STANDARD CONDITIONS OF SALE, WHICH ARE INCLUDED IN THE APPLICABLE DISTRIBUTOR OR OTHER SALES AGREEMENT, PRINTED ON THE BACK OF ORDER ACKNOWLEDGMENTS AND INVOICES, AND AVAILABLE UPON REQUEST. ALTHOUGH ANY INFORMATION, RECOMMENDATIONS, OR ADVICE CONTAINED HEREIN IS GIVEN IN GOOD FAITH, SUPPLIER MAKES NO WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, (i) THAT THE RESULTS DESCRIBED HEREIN WILL BE OBTAINED UNDER END-USE CONDITIONS, OR (ii) AS TO THE EFFECTIVENESS OR SAFETY OF ANY DESIGN INCORPORATING ITS PRODUCTS, MATERIALS, SERVICES, RECOMMENDATIONS OR ADVICE. EXCEPT AS PROVIDED IN SUPPLIER'S STANDARD CONDITIONS OF SALE, SUPPLIER AND ITS REPRESENTATIVES SHALL IN NO EVENT BE RESPONSIBLE FOR ANY LOSS RESULTING FROM ANY USE OF ITS MATERIALS, PRODUCTS OR SERVICES DESCRIBED HEREIN. Each user bears full responsibility for making its own determination as to the suitability of Supplier's materials, services, recommendations, or advice for its own particular use. Each user must identify and perform all tests and analyses necessary to assure that its finished parts incorporating Supplier's products, materials, or services will be safe and suitable for use under end-use conditions. Nothing in this or any other document, nor any oral recommendation or advice, shall be deemed to alter, vary, supersede, or waive any provision of Supplier's standard Conditions of Sale or this Disclaimer, unless any such modification is specifically agreed to in a writing signed by Supplier. No statement contained herein concerning a possible or suggested use of any material, product, service or design is intended, or should be construed, to grant any license under any patent or other intellectual property right of Supplier covering such use or design, or as a recommendation for the use of such material, product, service or

design in the infringement of any patent or other intellectual property right.

The use of the "™" symbol designates registered or unregistered trademarks of Momentive Performance Materials Inc. or its affiliated companies. Momentive and the Momentive logo are trademarks of Momentive Performance Materials Inc.