

CF1251

CF1251

Description

SF1236, SF1276 and CF1251 are blends of a high molecular weight silicone polymer dispersed in a low viscosity silicone fluid. These blends provide enhanced performance in personal care products.

SF1236 is a blend of silicone gum in a 5 centistoke polydimethylsiloxane fluid. **SF1276** is a blend of silicone gum in a 20 centistoke polydimethylsiloxane fluid. **CF1251** is a blend of silicone gum in a 350 centistoke polydimethylsiloxane fluid.

INCI NAMES

SF1236 Dimethicone SF1276 Dimethicone CF1251 Dimethicone

Key Features and Benefits

Hair Care

- Provides excellent wet and dry combing
- Improves softness
- Enhances shine
- Provides improved manageablity and conditioning

Skin Care

- Imparts a soft, smooth, velvety feel
- Provides excellent emolliency
- Imparts a durable film
- Improves spreadibility, applicaton and rub-in Antiwhitening/Antisoaping agent

Typical Physical Properties

| Alternative Action of the control of | | | |
|--|-------------|------------|----------------|
| Property | SF1236 | SF1276 | CF1251 |
| Silicone Content, % | 100 | 100 | 100 |
| Viscosity @ 25°C, cPs | 3000-5500 | 7500-10000 | 350000- 850000 |
| Color | Clear | Clear | Clear |
| Specific Gravity, 25°C | 0.914-0.934 | 0.9621 | 0.965-0.985 |
| Refractive Index @25°C | 1.393-1.403 | 1.4029 | 1.400-1.410 |

SOLUBILITY DATA

Key

I = Insoluble at < 1% by weight

PS = Partially Soluble at 1-10% by weight

S = Soluble at > 10% by weight

| Solvent Type | Material | SF1236 | SF1276 | CF1251 |
|------------------------------|---|--------|--------|--------|
| Highly Polar | Water | I | I | I |
| Hydrocarbon & Vegetable Oils | Mineral Oil 65/75 SUS | I | I | I |
| | Mineral Oil 220/210 SUS | I | I | I |
| | Petrolatum | I | I | I |
| | Cottonseed (Gossypium) Oil | I | I | I |
| | Castor (Ricinus Communis)Oil | I | I | I |
| | Sunflower (Helianthus Annuus) Seed Oil | I | | I |
| | Maleated Soybean Oil | I | I | I |
| | Wheat (Triticum Vulgare) Germ Oil | I | I | I |

| Alcohols & Glycols | | Cetyl Alcohol | | I | I | I |
|--------------------|-------------------------------------|---------------------------------|---|---|----|---|
| | | Ethanol | | 1 | I | I |
| | | SD Alcohol 40 | | I | I | I |
| | | Isopropyl Alcohol | | I | I | I |
| | | Mineral Spirits | | S | S | I |
| | | 2-Ethyl-Hexanol | | I | I | I |
| | | Lauryl Alcohol | | I | Ι | I |
| | | Stearyl Alcohol | | I | I | I |
| | | Ethylene Glycol | | I | I | I |
| | | Propylene Glycol | | 1 | Ι | I |
| | | Glycerin | | 1 | Ι | I |
| Esters | | Isopropyl Palmitate | | I | I | I |
| | | Isopropyl Myristate | | S | S | I |
| | | Myristyl Propionate | | 1 | Ι | I |
| | | PPG-2 Myristyl Ether Propionate | | 1 | Ι | I |
| Silicones | Dimeth | nicone (SF96-350) | S | S | S | |
| | Cyclop | entasiloxane (SF1202) | S | S | PS |) |
| | Diisost | earoyl Trimethylpropane | | | | |
| | Siloxy Silicate (SF1318) | | | | | |
| | Phenyl | Trimethicone (SF1550) | S | S | I | |
| Waxes | Paraffin | | I | I | I | |
| | Ozokerite | | I | I | I | |
| | Candelilla (Euphorbia Cerifera) Wax | | I | I | | |
| | Beeswax | | I | I | | |
| | Carnuba (Copernicia Cerifera) Wax | | I | I | | |
| Sunscreens | Octyl Dimethyl PABA | | I | I | I | |
| | Benzophenone-3 | | I | I | I | |
| | Octyl Methoxycinnamate | | I | I | I | |
| | Octyl Salicylate | | I | I | I | |
| Pigments | D& C Orange No. 5 | | I | I | I | |
| | D& C Red No. 21 | | I | I | | |
| | Iron Ox | xides | I | I | I | |
| Lanolin | Lanolin | | I | I | | |
| Other | Tocopheryl Acetate | | I | I | | |

Potential Applications

- Protective Skin Products
- Sunscreen Products
- Facial Make-Up
- Lotion
- Color Cosmetics
- 2/1 Shampoos
- Hair Conditioners

Patent Status

Standard copy to come

Product Safety, Handling and Storage

The warranty period for SF1236 is 24 months from date of shipment from Momentive Performance Materials if stored in the original unopened container at 25°C (77°F). The warranty period for SF1276 and CF1251 is 12 months from date of shipment from Momentive Performance Materials if stored in the original unopened container at 25°C (77°F).

Standard copy to come

Limitations

Standard copy to come

Contact Information

Email

commercial.services@momentive.com

| Telephone | | | |
|-----------------|------------------|---|------------------|
| Americas | Latin America | EMEAI- Europe, Middle East, Africa & India | ASIA PACIFIC |
| +1 800 295 2392 | Brazil | Europe | China |
| Toll free* | +55 11 4534 9650 | +390510924300 | 800 820 0202 |
| +704 805 6946 | Direct Number | Direct number | Toll free |
| Direct Number | | | +86 21 3860 4892 |
| | | | Direct number |
| *All American | Mexico | India, Middle East & | Japan |
| countries | +52 55 2169 7670 | Africa | +81 3 5544 3111 |
| | Direct Number | + 91 44 71212207 | Direct number |
| | | Direct number* | |
| | | *All Middle Eastern | Korea |
| | | countries, Africa, India, | +82 2 6201 4600 |
| | | | |

For literature and technical assistance, visit our website at: www.momentive.com

DISCLAIMER:

THE MATERIALS, PRODUCTS AND SERVICES OF MOMENTIVE PERFORMANCE MATERIALS INC. AND ITS SUBSIDIARIES AND AFFILIATES (COLLECTIVELY "SUPPLIER"), ARE SOLD SUBJECT TO SUPPLIER'S STANDARD CONDITIONS OF SALE, WHICH ARE INCLUDED IN THE APPLICABLE DISTRIBUTOR OR OTHER SALES AGREEMENT, PRINTED ON THE BACK OF ORDER ACKNOWLEDGMENTS AND INVOICES, AND AVAILABLE UPON REQUEST. ALTHOUGH ANY INFORMATION, RECOMMENDATIONS, OR ADVICE CONTAINED HEREIN IS GIVEN IN GOOD FAITH, SUPPLIER MAKES NO WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, (i) THAT THE RESULTS DESCRIBED HEREIN WILL BE OBTAINED UNDER END-USE CONDITIONS, OR (ii) AS TO THE EFFECTIVENESS OR SAFETY OF ANY DESIGN INCORPORATING ITS PRODUCTS, MATERIALS, SERVICES, RECOMMENDATIONS OR ADVICE. EXCEPT AS PROVIDED IN SUPPLIER'S STANDARD CONDITIONS OF SALE. SUPPLIER AND ITS REPRESENTATIVES SHALL IN NO EVENT BE RESPONSIBLE FOR ANY LOSS RESULTING FROM ANY USE OF ITS MATERIALS, PRODUCTS OR SERVICES DESCRIBED HEREIN. Each user bears full responsibility for making its own determination as to the suitability of Supplier's materials, services,

recommendations, or advice for its own particular use. Each user must identify and perform all tests and analyses necessary to assure that its finished parts incorporating Supplier's products, materials, or services will be safe and suitable for use under end-use conditions. Nothing in this or any other document, nor any oral recommendation or advice, shall be deemed to alter, vary, supersede, or waive any provision of Supplier's standard Conditions of Sale or this Disclaimer, unless any such modification is specifically agreed to in a writing signed by Supplier. No statement contained herein concerning a possible or suggested use of any material, product, service or design is intended, or should be construed, to grant any license under any patent or other intellectual property right of Supplier covering such use or design, or as a recommendation for the use of such material, product, service or design in the infringement of any patent or other intellectual property right.

The use of the "TM" symbol designates registered or unregistered trademarks of Momentive Performance Materials Inc. or its affiliated companies. Momentive and the Momentive logo are trademarks of Momentive Performance Materials Inc.