

Silopren™ Gel 6209FC

Description

Silopren Gel 6209FC is a kit matched easily pourable, solvent free, clear and colourless two-component silicone gel. After mixing the A and the B part at a mix ratio of 1: 1 the material cures very fast at room temperature by an addition reaction to a tacky silicone gel with excellent vibration dampening properties.

Key Features and Benefits

- Convenient 1: 1 mixing by weight
- Low viscosity, free of solvents
- Fast room temperature cure
- Soft, tacky gel, sticking to many substrates
- Mechanical shock and vibration damping properties
- Useful temperature range –50°C to 150 °C

Typical Physical Properties

Uncured Properties		Gel 6209FC (A)	Gel 6209FC (B)
Colour		Clear, colourless	Clear, colourless
Consistency		Easily pourable	Easily pourable
Viscosity	mPa.s	1000	1000
Specific gravity	g/cm ³	0.98	0.98
Uncured / Mixed properties		Gel 6209FC	
Mix ratio		1:1	

Colour		Clear, colourless
Consistency		Easily pourable
Viscosity	mPa.s	1000
Work time @ 23 °C *	Minutes	30

Cured properties (Cured 1 hr @ 100 °C)		
Mechanical		Gel 6209FC
Penetration, 1/4 cone (9.4g), 1/10mm		85
Density	g/cm ³	0.98
Refractive index		1.41
Electrical		
Dielectric strength	kV/mm	20
Dielectric constant (@ 60 Hz)		2.8
Dissipation factor (@ 60 Hz)		0.001
Volume resistivity	Ω . cm	2.0 x 10 ¹⁵
Tracking Resistance	CTI	>600
Thermal		
Useful temp. range	°C	-50 to 150
Thermal conductivity *	W/m . K	0.17
Coefficient of Linear Expansion *	1/ K	30 x 10 ⁻⁵

Typical properties are not to be used as or to develop specifications.

Potential Applications

Silopren Gel 6209FC is specially developed for electronic potting applications such as hybrid IC insulation, potting of power modules and sensors when fast cure at room temperature is required.

Patent Status

여기에 포함된 어떠한 내용도 관련 특허가 없음을 의미하거나 특허 소유자의 허가 없이

특허에서 다루는 발명을 실행하기 위한 허가, 유도 또는 권고를 구성하는 것으로 해석되어서는 안됩니다.

Product Safety, Handling and Storage

Customers should review the latest Safety Data Sheet (SDS) and label for product safety information, safe handling instructions, personal protective equipment if necessary, emergency service contact information, and any special storage conditions required for safety. Momentive Performance Materials (MPM) maintains an around-the-clock emergency service for its products. SDS are available at www.momentive.com or, upon request, from any MPM representative. For product storage and handling procedures to maintain the product quality within our stated specifications, please review Certificates of Analysis, which are available in the Order Center. Use of other materials in conjunction with MPM products (for example, primers) may require additional precautions. Please review and follow the safety information provided by the manufacturer of such other materials.

Limitations

Customers must evaluate Momentive Performance Materials products and make their own determination as to fitness of use in their particular applications.

Contact Information

Email

commercial.services@momentive.com

Telephone

Americas	Latin America	EMEAI- Europe, Middle East, Africa & India	ASIA PACIFIC
+1 800 295 2392 Toll free*	Brazil +55 11 4534 9650 Direct Number	Europe +390510924300 Direct number	China 800 820 0202 Toll free +86 21 3860 4892 Direct number
*All American	Mexico	India, Middle East & Africa	Japan

countries	+52 55 2169 7670	+ 91 44 71212207	+81 3 5544 3111
	Direct Number	Direct number*	Direct number
		*All Middle Eastern	Korea
		countries, Africa, India,	+82 2 6201 4600

For literature and technical assistance, visit our website at: www.momentive.com

DISCLAIMER:

THE MATERIALS, PRODUCTS AND SERVICES OF MOMENTIVE PERFORMANCE MATERIALS INC. AND ITS SUBSIDIARIES AND AFFILIATES (COLLECTIVELY “SUPPLIER”), ARE SOLD SUBJECT TO SUPPLIER’S STANDARD CONDITIONS OF SALE, WHICH ARE INCLUDED IN THE APPLICABLE DISTRIBUTOR OR OTHER SALES AGREEMENT, PRINTED ON THE BACK OF ORDER ACKNOWLEDGMENTS AND INVOICES, AND AVAILABLE UPON REQUEST. ALTHOUGH ANY INFORMATION, RECOMMENDATIONS, OR ADVICE CONTAINED HEREIN IS GIVEN IN GOOD FAITH, SUPPLIER MAKES NO WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, (i) THAT THE RESULTS DESCRIBED HEREIN WILL BE OBTAINED UNDER END-USE CONDITIONS, OR (ii) AS TO THE EFFECTIVENESS OR SAFETY OF ANY DESIGN INCORPORATING ITS PRODUCTS, MATERIALS, SERVICES, RECOMMENDATIONS OR ADVICE. EXCEPT AS PROVIDED IN SUPPLIER’S STANDARD CONDITIONS OF SALE, SUPPLIER AND ITS REPRESENTATIVES SHALL IN NO EVENT BE RESPONSIBLE FOR ANY LOSS RESULTING FROM ANY USE OF ITS MATERIALS, PRODUCTS OR SERVICES DESCRIBED HEREIN. Each user bears full responsibility for making its own determination as to the suitability of Supplier’s materials, services, recommendations, or advice for its own particular use. Each user must identify and perform all tests and analyses necessary to assure that its finished parts incorporating Supplier’s products, materials, or services will be safe and suitable for use under end-use conditions. Nothing in this or any other document, nor any oral recommendation or advice, shall be deemed to alter, vary, supersede, or waive any provision of Supplier’s standard Conditions of Sale or this Disclaimer, unless any such modification is specifically agreed to in a writing signed by Supplier. No statement contained herein concerning a possible or suggested use of any material, product, service or design is intended, or should be construed, to grant any license under any patent or other intellectual property right of Supplier covering such use or design, or as

a recommendation for the use of such material, product, service or design in the infringement of any patent or other intellectual property right.

*Silopren™는 Momentive Performance Materials Inc.의 상표입니다.

The use of the "™" symbol designates registered or unregistered trademarks of Momentive Performance Materials Inc. or its affiliated companies. Momentive and the Momentive logo are trademarks of Momentive Performance Materials Inc.