

Silwet™ HS-312

Silwet* HS-312

Description

Silwet HS-312 spreader is a new, hydrolytically stable silicone with a broad pH stability range allowing formulators many options to incorporate it as a cost-effective adjuvant in many in-can pesticide products.

Silwet HS-312 spreader is an excellent candidate to consider for superb spreading performance and extended stability in water-based formulations between pH 3 to pH 12. This product offers excellent performance as a spreader, relative to commercial surfactants, for the effective delivery of many in-can pesticides with lower spray application rates. In addition, Silwet HS-312 spreader is used at much lower rates compared to conventional surfactant adjuvants.

Silwet HS-312 spreader is compatible with many agrochemical components and can therefore be dispersed into water-based agricultural formulations yielding products with excellent storage stability.

Key Features and Benefits

- 4-10X more surface spreading than surfactant adjuvants
- Improves spray coverage on crops
- Promotes spray volume reduction
- Compatible with Ag formulations
- Excellent stability with Ag formulations between pH 3-12

Typical Physical Properties

Appearance	Yellow to amber liquid
Surface Tension, mN/m (0.1 wt%) ^(a)	26.7
Spreading Diameter, mm	35
Viscosity 25°C, cps (LVT No 3, 100 rpm)	70
Cloud Point, °C	42
Specific Gravity	1.0
pH Stability	3-12

(a) Wilhelmy Plate Method; solutions prepared in 0.005M NaCl

Product Usage

Silwet HS-312 spreader is a cost-effective spreader that can be used in in-can pesticide products in the 3-12 pH range. It can be added as a component directly to such formulations to provide better spreading during spray application.

The addition levels of Silwet HS-312 spreader are dependent on the level of spreading required in the spray application of the pesticide. A recommended use rate is 5% of the total pesticide formulation, or 0.05% - 0.20% of the tank-mix mixture.

Processing Recommendations

Performance Data

Because the Silwet HS-312 spreader has very low surface tension, the contact angle of spray solutions on leaf surfaces is reduced compared to other surfactant adjuvants. This important property is shown in Figure 1 below, which illustrates Silwet HS-312 spreader having less than 5° contact angle relative to the Octylphenol Ethoxylate containing 10 EO units (OPE-10), having a 31° contact angle. It is also important to note that the lower Silwet HS-312 spreader contact angle is achieved at much lower concentrations compared to the OPE-10 surfactant concentration.

Figure 1: Contact Angles of Spreader Adjuvants



Figure 2 illustrates the excellent wetting properties of the Silwet HS-312 spreader. Compared to OPE-10 at equal concentrations, Silwet HS-312 spreader has 5 times larger spread diameter, which results in improved surface coverage during spray applications. Even at significantly lower concentrations, Silwet HS-312 spreader has better spreading performance than conventional adjuvants, which can potentially lower spray volumes during the application of pesticides to a crop.

Figure 2: Spread Diameter vs. Adjuvant Use




Figure 3 illustrates an improvement in efficacy of a 1% glyphosate treatment on Velvetleaf (*Abutilion theophrasti*), when using Silwet HS-312 spreader. Plants grown indoors were treated at the 2 - 4 leaf stage with 1% glyphosate, using a track sprayer at a relative spray volume of 100 L/ha. Silwet HS-312 spreader was included as an adjuvant at 0.1% rate. Rain (2.5 cm) was applied two hours after treatment. A visual assessment was made at 7 and 14 days after treatment as compared to an untreated control.



Patent Status

US and foreign Patent applications pending

Standard copy to come

Product Safety, Handling and Storage

Standard copy to come

Limitations

Standard copy to come

Contact Information

Email

commercial.services@momentive.com

Telephone

Americas

+1 800 295 2392

Toll free*

+704 805 6946

Direct Number

*All American countries

Latin America

Brazil

+55 11 4534 9650

Direct Number

Mexico

+52 55 2169 7670

Direct Number

EMEAI- Europe, Middle East, Africa & India

Europe

+390510924300

Direct number

India, Middle East & Africa

+ 91 44 71212207

Direct number*

***All Middle Eastern countries, Africa, India,**

ASIA PACIFIC

China

800 820 0202

Toll free

+86 21 3860 4892

Direct number

Japan

+81 3 5544 3111

Direct number

Korea

+82 2 6201 4600

For literature and technical assistance, visit our website at: www.momentive.com

DISCLAIMER:

THE MATERIALS, PRODUCTS AND SERVICES OF MOMENTIVE PERFORMANCE MATERIALS INC. AND ITS SUBSIDIARIES AND AFFILIATES (COLLECTIVELY “SUPPLIER”), ARE SOLD SUBJECT TO SUPPLIER’S STANDARD CONDITIONS OF SALE, WHICH ARE INCLUDED IN THE APPLICABLE DISTRIBUTOR OR OTHER SALES AGREEMENT, PRINTED ON THE BACK OF ORDER

ACKNOWLEDGMENTS AND INVOICES, AND AVAILABLE UPON REQUEST. ALTHOUGH ANY INFORMATION, RECOMMENDATIONS, OR ADVICE CONTAINED HEREIN IS GIVEN IN GOOD FAITH, SUPPLIER MAKES NO WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, (i) THAT THE RESULTS DESCRIBED HEREIN WILL BE OBTAINED UNDER END-USE CONDITIONS, OR (ii) AS TO THE EFFECTIVENESS OR SAFETY OF ANY DESIGN INCORPORATING ITS PRODUCTS, MATERIALS, SERVICES, RECOMMENDATIONS OR ADVICE. EXCEPT AS PROVIDED IN SUPPLIER'S STANDARD CONDITIONS OF SALE, SUPPLIER AND ITS REPRESENTATIVES SHALL IN NO EVENT BE RESPONSIBLE FOR ANY LOSS RESULTING FROM ANY USE OF ITS MATERIALS, PRODUCTS OR SERVICES DESCRIBED HEREIN. Each user bears full responsibility for making its own determination as to the suitability of Supplier's materials, services, recommendations, or advice for its own particular use. Each user must identify and perform all tests and analyses necessary to assure that its finished parts incorporating Supplier's products, materials, or services will be safe and suitable for use under end-use conditions. Nothing in this or any other document, nor any oral recommendation or advice, shall be deemed to alter, vary, supersede, or waive any provision of Supplier's standard Conditions of Sale or this Disclaimer, unless any such modification is specifically agreed to in a writing signed by Supplier. No statement contained herein concerning a possible or suggested use of any material, product, service or design is intended, or should be construed, to grant any license under any patent or other intellectual property right of Supplier covering such use or design, or as a recommendation for the use of such material, product, service or design in the infringement of any patent or other intellectual property right.

*Silwet™ é uma marca registrada da Momentive Performance Materials Inc.

The use of the "™" symbol designates registered or unregistered trademarks of Momentive Performance Materials Inc. or its affiliated companies. Momentive and the Momentive logo are trademarks of Momentive Performance Materials Inc.